

CULLAPLAST

A water-borne premium quality textured protective and decorative finish. For use on most exterior and interior flat (not textured) masonry surfaces and exterior grade building boards. Provides a tough resilient weatherproof finish. A variety of patterns can be achieved.

AVAILABILITY

Colour range Refer to current Sandtex Trade Literature.

Packaging 15 Kilogram.

PROPERTIES

Drying time Under normal drying conditions surface dry within 12 hours. Through dry within 24-48 hours.

Finish Matt, textured (aggregate filled).

Composition Pigment: Titanium Dioxide, light fast coloured pigments and extenders
Binder: Vinyl acetate copolymer.
Solvent: Water.

Spreading rate 2.5 - 3 Kilograms per m². (5-6m² per 15 Kilogram pack).

Volume solids 73% White other colours will vary

Flash point Not applicable.

VOC content EU limit value for this product (cat.A/c): 75 g/l (2007) / 40 g/l (2010)
This product contains max. 5 g/l VOC.

Limitations Do not apply when there is a risk of rain, air or substrate temperatures are likely to fall below 8°C or when the relative humidity is above 80% during application or the drying period.

PREPARATION

New surfaces All surfaces must be sound, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. Surfaces with suction (porous surfaces) should be treated with an application of Sandtex Trade Stabilising Solution.

Previously decorated surfaces

All surfaces must be sound, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. Remove all loose, and failing or suspect material by scraping or brushing with a stiff bristle brush (not wire) to a sound edge. Organic growth must be removed and the areas treated with Sandtex Trade Fungicide. For surfaces in poor condition mechanical means may be necessary e.g. pressure washing between 1500-2000 psi (102-136 bar), proprietary paint removal system, wet or dry grit blasting. Care must be taken not to damage the underlying surface. Fill cracks and small defects in masonry surfaces with Sandtex Trade Ready Mixed Filler or Exterior Easiplast and finish to match existing. Stabilise all bare, filled and previously decorated chalking areas with an application of Sandtex Trade Stabilising Solution. Wash any soundly adhering gloss painted surfaces with hot water and liquid detergent solution to remove any contaminants frequently changing the water. Wet abrade to provide a key. Rinse thoroughly with clean water to remove all residues.

COATING SYSTEM Apply in one coat to primed surfaces. Maintain a wet edge. For advice on the completion of large areas please contact our Customer Relations Team on the tel. no. provided below.

APPLICATION Prime all areas to be decorated with a matching colour of Sandtex Trade Fine Textured Matt. Allow a minimum drying time of 24 hours in normal drying conditions. Stir Sandtex Trade Cullaplast well before use. Apply by hawk and trowel to the thickness of the coarse aggregate and texture using a Sandtex Cullaplast Float. For spray application use a Portaspray twin compressor and hopper gun set up. Mask as necessary with a wet strength masking paper.

CLEANING Return surplus material to container. Wash with clean water immediately after use.

MAINTENANCE INFORMATION FOR CDM FILE

Between maintenance redecoration surfaces may be washed with a warm water and liquid detergent solution to remove surface dirt.

HEALTH AND SAFETY Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact the Customer Relations Team. When preparing the surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other Sandtex products are freely available from the place of purchase or the address below. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.

GENERAL INFORMATION

Apply all products in accordance with BS 6150: 2006 Code of practice for painting of buildings and BS 8000: Part 12: 1989 Code of practice for decorative wallcoverings and painting. Under normal and frost free conditions this product will remain usable for up to two years if stored correctly and unopened.

Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. Final results cannot be guaranteed by the manufacturer as it has no control over the conditions under which its products are applied.

For help or more information contact our Customer Relations Team on 0845 372 3425. Before using this product please ensure you have the latest information. The information is correct at date of issue July 2008.



Sandtex Trade
Hollins Road, Darwen, Lancs BB3 0BG
Tel: 0845 372 3425 Fax: 0845 372 3426 Email: info@sandtextrade.co.uk
Website: www.sandtextrade.co.uk