

**PVC-u PRIMER**

A water-borne flexible primer specially formulated to provide superior adhesion to new & weathered PVC-u building components.

AVAILABILITY

**Colour range** White.

**Packaging** 1 litre.

PROPERTIES

**Drying time** Under normal drying conditions dry in 1 hour and recoatable after 4 hours.

**Composition** Pigment: Titanium Dioxide & mineral extenders.  
Binder: Acrylic copolymer.  
Solvent: Water.

**Spreading rate** 12m<sup>2</sup> per litre on smooth surfaces.

**Wet film thickness** 83 micrometres at 12m<sup>2</sup> per litre.

**Dry film thickness** 20 micrometres at 12m<sup>2</sup> per litre

**Volume solids** 35%

**Flash point** Not applicable.

**VOC content** EU limit value for this product (cat.A/i): 140 g/l (2007) / 140 g/l (2010)  
This product contains max. 59 g/l VOC.

**Limitations** Do not apply when there is a risk of rain, air or substrate temperatures are likely to fall below 8°C or when the relative humidity is above 80% during application or the drying period.

PREPARATION

**New and weathered surfaces**

Clean all surfaces using Sandtex Trade PVC-u Cleaner in accordance with the manufacturers instructions.

**Previously decorated surfaces**

All surfaces must be suitably dry, and free from anything that will interfere with the adhesion of the materials to be applied. Remove all loose, and failing or suspect / coatings back to a firm edge. Lightly abrade and feather all edges. Clean all exposed surfaces using Sandtex Trade PVC-u Cleaner in accordance with the manufacturers instructions.

COATING SYSTEM

Apply two coats of Sandtex Trade PVC-u Primer to new surfaces and previously painted surfaces. Finish as required.  
Not suitable for garden furniture.

APPLICATION

Stir well before use. Apply by brush to an even thickness (a fine, soft long filament synthetic brush gives best results). Can be applied by (woven / short pile) roller.

#### CLEANING EQUIPMENT

Return surplus material to container. Wash with clean water immediately after use.

#### MAINTENANCE INFORMATION FOR CDM FILE

Between maintenance redecoration surfaces may be washed with a warm water and liquid detergent solution to remove surface dirt.

**HEALTH AND SAFETY** Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact the Customer Relations Team. When preparing the surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other Sandtex products are freely available from the place of purchase or the address below. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.

#### GENERAL INFORMATION

Apply all products in accordance with BS 6150: 2006 Code of practice for painting of buildings and BS 8000: Part 12: 1989 Code of practice for decorative wallcoverings and painting. Under normal and frost free conditions this product will remain usable for up to two years if stored correctly and unopened.

Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. Final results cannot be guaranteed by the manufacturer as it has no control over the conditions under which its products are applied.

For help or more information contact our Customer Relations Team on 0845 372 3425. Before using this product please ensure you have the latest information. The information is correct at date of issue July 2008.



#### **Sandtex Trade**

Hollins Road, Darwen, Lancs BB3 0BG

Tel: 0845 372 3425 Fax: 0845 372 3426 Email: [info@sandtextrade.co.uk](mailto:info@sandtextrade.co.uk)  
Website: [www.sandtextrade.co.uk](http://www.sandtextrade.co.uk)