

TECHNICAL DATA SHEET

Sandtex[®]

READY MIXED FILLER

Sandtex Ready Mixed Filler is an easy to use ready mixed filler suitable for both interior and exterior use. When applied as directed, the filler dries to a smooth but tough crack resistant finish, which may be painted, papered or stained.

AREAS FOR USE Plaster, Brick, Stone, Wood, Render.

AVAILABILITY

Colour Range White

Packaging 500gram plastic container.

PROPERTIES

Drying Time 1-8 hours depending on depth and temperature.

Composition Pigments, reinforcing fillers & styrene acrylic copolymer.

Spreading Rate Variable depending on width and depth of filling or making good.

Maximum Fill Up to a maximum of 9mm per application, further layers may be built up.

Maximum Width 25mm.

Volume Solids 85-90%

Flash Point Not applicable.

VOC Content Not applicable

Limitations Do not apply when there is a risk of rain, or when air or substrate temperatures are likely to fall below 5°C. Not suitable for repairs to permanently wet areas. Do not use to fill plastics or metal.

PREPARATION

New surfaces All surfaces must be clean, sound, dry, free from dust, grease and all other forms of surface contamination. Prime all nail or screw heads with Sandtex Trade Rust Inhibiting Primer Undercoat and allow to dry.

Previously decorated surfaces

All surfaces must be clean, sound, dry, free from dust, grease and all other forms of surface contamination. Remove all loose, failing or suspect material/coatings. Thoroughly abrade gloss painted surfaces to provide a key. Prime all nail or screw heads with Sandtex Trade Rust Inhibiting Primer Undercoat and allow to dry.

APPLICATION

Stir well and apply directly from the tub with a filling knife or spatula. Press the filler into the repair to a maximum depth of 9mm. For deeper cavities, apply in layers and allow each layer to dry (1 hour). Fill hole proud to allow for sanding and finish with a wet knife. Once dry, sand to a smooth finish. When used outdoors, seal repair with an oil based paint when fully dry.

CLEANING Wash tools and equipment with clean warm water immediately after use. Do not empty or wash the remains of Sandtex Ready Mixed Filler into drainage systems.

STORAGE Store between 5°C to 25°C temperatures and protect from frost.

HEALTH AND SAFETY Safe in normal use. Avoid inhalation of dust once dry. Do not eat or drink during use. Remove product with soap and water. If product enters eyes, rinse immediately with cold water and seek medical attention if irritation persists. If ingested, give plenty of water to drink and seek medical attention. Keep out of the reach of children. Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact the Sandtex Advice Centre. When preparing all surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other Crown Paints products are freely available to download from websites or the address below. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.

GENERAL INFORMATION

Apply all products in accordance with BS 6150: 2006 Code of practice for painting of buildings and BS 8000 : Part 12 : 1989 Code of practice for decorative wallcoverings and painting. Under normal and frost free conditions this product will remain usable for up to two years if stored correctly and unopened.

Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. Crown Paints is unable to guarantee results as it has no control over the conditions under which its products are applied.

Before using this product please ensure that you have the latest information.

For help or more information contact the Sandtex Advice Team on:

Tel: 0330 0240 303

Email: sandtexp@crownpaint.co.uk

Website: www.sandtexp.co.uk

The information is correct at date of issue November 2018

P O Box 37, Crown House, Hollins Road, Darwen, Lancashire, BB3 0BG
Tel: 01254 704951