



Technical Datasheet

FUNGICIDAL WASH

A ready to use fungicide solution for the treatment and prevention of organic growth on exterior undecorated and all previously decorated surfaces. Can also be used on interior surfaces. Approved under the Control of Pesticides Regulations 1966 for use as directed. HSE Certificate No. 10482.

AVAILABILITY	
Colour range	Clear
Packaging	2.5 and 5 litres
PROPERTIES	
Drying time (under normal drying conditions)	Allow to dry after application, timing can be anything from 20 minutes upwards depending on temperature and humidity.
Finish	Not applicable
Composition	Alkyl (C12-16) Dimethylbenzyl ammonium chloride (0.99% w/w) 2 – Phenylphenol (0.25% w/w)
Spreading rate	5 - 10m ² per litre depending on porosity of surface. On highly textured or porous surfaces the spreading rate will be greatly reduced.
Wet film thickness	Not applicable
Dry film thickness	Not applicable
Volume solids	Not applicable
Flash point	Not applicable
VOC content	Not applicable
Limitations	For use only as specified as a surface biocide
PREPARATION	
New surfaces and Previously decorated surfaces	All surfaces must be sound, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied.

COATING SYSTEM	Apply one coat as required, however where severe two applications may be necessary
APPLICATION	Always read the label before use and wear suitable protective equipment. Apply liberally with a nylon bristle brush, or non-atomising spray, scrub into surface, leave to dry. All signs of organic growth should then be removed with a scraper or stiff, bristle brush, not wire. Wash surfaces and allow to dry. Heavy long established organic growth is best removed by pressure washing between 1500-2000 psi (102-136 bar), wet or dry grit blasting. Care must be taken not to damage the underlying surface. Take care not to allow residues to run directly into fresh watercourses.
CLEANING	Wash with clean soapy water immediately after use.
HEALTH AND SAFETY	Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact the Customer Relations Team. When preparing the surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other Sandtex products are freely available from the place of purchase, the address below or visit sandtextrade.co.uk . Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.
STORAGE	Store upright and secure. Crown Paints cannot accept liability for damage caused by spillage or failure to follow manufacturer's instructions. Do not store below 5°C or above 40°C.
GENERAL INFORMATION	Apply all products in accordance with BS 6150: Code of practice for painting of buildings and BS 8000: Part 12: 1989 Code of practice for decorative wallcoverings and painting. Under normal and frost free conditions this product will remain usable for up to two years if stored correctly and unopened. Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. Final results cannot be guaranteed by the manufacturer as it has no control over the conditions under which its products are applied.

For help or more information contact our Customer Relations Team on 0330 024 0302. Before using this product please ensure you have the latest information

The information in this technical datasheet is correct at date of issue – July 2018

Sandtex

Crown Paints Limited, Hollins Road, Darwen, Lancashire BB3 0BG
Tel: 0330 024 0302 Email: info@sandtextrade.co.uk Website: sandtextrade.co.uk